

QUICK START INSTRUCTIONS:


#5260




1. INSERT MALE PORT (BLUE) ON CLAMP CABLE INTO FEMALE SLOT ON JUMP STARTER UNIT.



2. ONCE INSIDE, LIGHT ON CLAMP CABLE WILL FLASH RED & GREEN. IT'S LOOKING FOR A BATTERY.



3. ATTACH CLAMPS TO BATTERY. LIGHT ON CABLE SHOULD TURN SOLID GREEN. *



4. TURN ON VEHICLE'S IGNITION.



5. REMOVE CLAMP CABLE IMMEDIATELY. YOU SHOULD BE GOOD TO GO!



* USE THE BOOST TO GET THROUGH!

IF THE CLAMP CABLE LIGHT TURNS SOLID RED, THE BATTERY MAY BE TOO WEAK FOR THE JUMP TO RECOGNIZE. NO PROBLEM. SIMPLY HOLD THE RST PIN BUTTON* ON THE BOTTOM OF THE CLAMP CABLE FOR 3 SECONDS TO OVERRIDE.



POWER BUTTON IS FOR LCD DISPLAY AND FLASHLIGHT

YOU DO NOT NEED TO PRESS THE POWER BUTTON TO ACTIVATE THE JUMP FEATURE, IT IS ALWAYS READY TO GO. PRESS THE POWER BUTTON TO TURN ON THE LCD DISPLAY AND TO POWER ON THE USB PORTS FOR CHARGING DEVICES. HOLD BUTTON FOR 3 SECONDS - TURNS ON FLASHLIGHT, PRESS AGAIN - STROBE, PRESS AGAIN - SOS

WWW.BATTERYSAVER.COM
FACEBOOK: /SAVEABATTERY

510-471-6442

32121 W M-28 ECKERMAN, MI 49728
X: @THEBATTERYSAVER

QUICK START INSTRUCTIONS:


#5260




1. INSERT MALE PORT (BLUE) ON CLAMP CABLE INTO FEMALE SLOT ON JUMP STARTER UNIT.



2. ONCE INSIDE, LIGHT ON CLAMP CABLE WILL FLASH RED & GREEN. IT'S LOOKING FOR A BATTERY.



3. ATTACH CLAMPS TO BATTERY. LIGHT ON CABLE SHOULD TURN SOLID GREEN. *



4. TURN ON VEHICLE'S IGNITION.



5. REMOVE CLAMP CABLE IMMEDIATELY. YOU SHOULD BE GOOD TO GO!



* USE THE BOOST TO GET THROUGH!

IF THE CLAMP CABLE LIGHT TURNS SOLID RED, THE BATTERY MAY BE TOO WEAK FOR THE JUMP TO RECOGNIZE. NO PROBLEM. SIMPLY HOLD THE RST PIN BUTTON* ON THE BOTTOM OF THE CLAMP CABLE FOR 3 SECONDS TO OVERRIDE.



POWER BUTTON IS FOR LCD DISPLAY AND FLASHLIGHT

YOU DO NOT NEED TO PRESS THE POWER BUTTON TO ACTIVATE THE JUMP FEATURE, IT IS ALWAYS READY TO GO. PRESS THE POWER BUTTON TO TURN ON THE LCD DISPLAY AND TO POWER ON THE USB PORTS FOR CHARGING DEVICES. HOLD BUTTON FOR 3 SECONDS - TURNS ON FLASHLIGHT, PRESS AGAIN - STROBE, PRESS AGAIN - SOS

WWW.BATTERYSAVER.COM
FACEBOOK: /SAVEABATTERY

510-471-6442

32121 W M-28 ECKERMAN, MI 49728
X: @THEBATTERYSAVER

READ BEFORE USE:

#5260

WARNING:

1. READ THE INSTRUCTION MANUAL CAREFULLY BEFORE USING THIS UNIT.
2. JUMP IS FOR 12V VEHICLES ONLY. PLEASE DON'T JUMP OTHER VOLTAGES.
3. DO NOT USE THIS UNIT IF CLAMP CABLE IS DAMAGED.
4. THIS DOES NOT REPLACE A VEHICLE BATTERY.
5. DO NOT USE AS A BATTERY CHARGER! REMOVE IMMEDIATELY AFTER JUMP.
6. AFTER CRANKING BATTERY SUCCESSFULLY, REMOVE JUMP FROM BATTERY.
7. MAKE SURE TO CHECK ALL THE BATTERY CONNECTIONS ARE CLEAN BEFORE JUMP STARTING. MAKE SURE THE BATTERY CLAMPS ARE WELL CONNECTED. IF THE BATTERY TERMINALS ON THE VEHICLES ARE DIRTY OR CORRODED, THE POWER TRANSFER MAY BE LIMITED.
8. DO NOT JUMP START MORE THAN 3 TIMES IN A ROW.
9. REMOVE THE PRODUCT FROM THE VEHICLE BATTERY WITHIN 30 SECONDS OF JUMP STARTING. IF NOT, IT COULD LEAD TO DAMAGE TO THE BATTERY.
10. DO NOT CONNECT THE TWO CLAMPS TOGETHER.
11. DO NOT USE AS A TOY.
12. DO NOT ALLOW THE PRODUCT TO BECOME WET.
13. DO NOT IMMERSE PRODUCT IN WATER.
14. DO NOT DISASSEMBLE UNIT. FOR REPAIRS, PLEASE CONTACT US.
15. DO NOT EXPOSE TO EXTREME HEAT OR EXTREME COLD.
16. PRODUCT CONTAINS LITHIUM TYPE BATTERY

SPECIFICATIONS:

SIZE:	8.5" D X 4" W X 1.2" H
WEIGHT:	1.2 LBS
BATTERY CAPACITY:	24,000MAH (88.8W)
USB:	QC3.05V/3A, 9V/2A. 12V/1.65A
INPUT:	TYPE-C 5V/3A
FULL CHARGE TIME:	4 - 5 HOURS
STARTING CURRENT:	2000A
PEAK CURRENT:	4000A
OPERATING TEMPERATURE:	-4°F - 140°F

INCLUDED PARTS:

HOST JUMP STARTER #5260 - QTY:	1
AC POWER CABLE - QTY:	1
USB TO TYPE-C CABLE - QTY:	1
INTELLIGENT JUMP CABLE - QTY:	1
PADDED CARRYING CASE - QTY:	1

WWW.BATTERYSAVER.COM
FACEBOOK: /SAVEABATTERY

510-471-6442

32121 W M-28 ECKERMAN, MI 49728
X: @THEBATTERYSAVER

READ BEFORE USE:

#5260

WARNING:

1. READ THE INSTRUCTION MANUAL CAREFULLY BEFORE USING THIS UNIT.
2. JUMP IS FOR 12V VEHICLES ONLY. PLEASE DON'T JUMP OTHER VOLTAGES.
3. DO NOT USE THIS UNIT IF CLAMP CABLE IS DAMAGED.
4. THIS DOES NOT REPLACE A VEHICLE BATTERY.
5. DO NOT USE AS A BATTERY CHARGER! REMOVE IMMEDIATELY AFTER JUMP.
6. AFTER CRANKING BATTERY SUCCESSFULLY, REMOVE JUMP FROM BATTERY.
7. MAKE SURE TO CHECK ALL THE BATTERY CONNECTIONS ARE CLEAN BEFORE JUMP STARTING. MAKE SURE THE BATTERY CLAMPS ARE WELL CONNECTED. IF THE BATTERY TERMINALS ON THE VEHICLES ARE DIRTY OR CORRODED, THE POWER TRANSFER MAY BE LIMITED.
8. DO NOT JUMP START MORE THAN 3 TIMES IN A ROW.
9. REMOVE THE PRODUCT FROM THE VEHICLE BATTERY WITHIN 30 SECONDS OF JUMP STARTING. IF NOT, IT COULD LEAD TO DAMAGE TO THE BATTERY.
10. DO NOT CONNECT THE TWO CLAMPS TOGETHER.
11. DO NOT USE AS A TOY.
12. DO NOT ALLOW THE PRODUCT TO BECOME WET.
13. DO NOT IMMERSE PRODUCT IN WATER.
14. DO NOT DISASSEMBLE UNIT. FOR REPAIRS, PLEASE CONTACT US.
15. DO NOT EXPOSE TO EXTREME HEAT OR EXTREME COLD.
16. PRODUCT CONTAINS LITHIUM TYPE BATTERY

SPECIFICATIONS:

SIZE:	8.5" D X 4" W X 1.2" H
WEIGHT:	1.2 LBS
BATTERY CAPACITY:	24,000MAH (88.8W)
USB:	QC3.05V/3A, 9V/2A. 12V/1.65A
INPUT:	TYPE-C 5V/3A
FULL CHARGE TIME:	4 - 5 HOURS
STARTING CURRENT:	2000A
PEAK CURRENT:	4000A
OPERATING TEMPERATURE:	-4°F - 140°F

INCLUDED PARTS:

HOST JUMP STARTER #5260 - QTY:	1
AC POWER CABLE - QTY:	1
USB TO TYPE-C CABLE - QTY:	1
INTELLIGENT JUMP CABLE - QTY:	1
PADDED CARRYING CASE - QTY:	1

WWW.BATTERYSAVER.COM
FACEBOOK: /SAVEABATTERY

510-471-6442

32121 W M-28 ECKERMAN, MI 49728
X: @THEBATTERYSAVER