

# MILITARY VEHICLES,

AIRCRAFT, DIESEL TRUCKS, RVS & OTHER 24 VOLT SYSTEMS

**50 WATT CHARGER, MAINTAINER & TESTER**

**24 VOLT**

**50 WATT**

**2 - 4 LARGE  
BATTERIES**

# CHARGERS

**& MAINTAINERS WITH BUILT-IN DIGITAL BATTERY TESTER**



#2365L-24

- Capable of Maintaining Several Batteries in a 24 Volt System
- Pulse Desulfation Technology -- Extends Battery Life
- Built-in LCD Digital Battery Tester (Tests The Battery, Load Tests & Tests The Charging System)
- Prevents Premature Battery Replacement with Proper Use
- Perfect for Long-Term Maintaining Once Maintainer Reaches FULL
- Works with SLA, GEL, Dry Cell, AGM, Deep Cycle, and Spiral Cell Batteries.
- Safe! Reverse Polarity Protection, No-Sparks

## SPECIFICATIONS:

**INPUT CHARACTERISTICS:** AC INPUT: 90 - 264V AC **FREQUENCY:** 47Hz - 63 Hz

**INPUT CURRENT:** 50 WATTS **HOLD UP TIME:** 8mSEC

**PROTECTION:** INPUT FUSED .750 AMPS (OC) OVER CURRENT (OV) OVER VOLTAGE (SC) SHORT CIRCUIT (RP) REVERSE POLARITY

**OUTPUT CHARACTERISTICS:** 27.8 VDC 2.08 AMPS - 50 WATT (P/N 2365L-24)

**RIPPLE & NOISE** 120 mV or less

**ENVIRONMENT:** 0 - 40 DEGREES(C), 20 - 80% HUMIDITY

**WARRANTY:** 12 MONTH LIMITED WARRANTY

**DIMENSIONS:** 2.5 LBS - 5.75" X 3.25" X 1.75"



## Included Cables:

6' Alligator Clip-On Cable,  
6' Terminal LUG Cable  
6' AC Power Cable  
& Mounting Bracket

**50 WATT CHARGER, MAINTAINER & TESTER**

**36 VOLT**

**50 WATT**

**3 - 6 LARGE  
BATTERIES**

# CHARGERS

**& MAINTAINERS WITH BUILT-IN DIGITAL BATTERY TESTER**



#2365L-36

- Capable of Maintaining Several Batteries in a 36 Volt System
- Pulse Desulfation Technology -- Extends Battery Life
- Built-in LCD Digital Battery Tester (Tests The Battery, Load Tests & Tests The Charging System)
- Prevents Premature Battery Replacement with Proper Use
- Perfect for Long-Term Maintaining Once Maintainer Reaches FULL
- Works with SLA, GEL, Dry Cell, AGM, Deep Cycle, and Spiral Cell Batteries.
- Safe! Reverse Polarity Protection, No-Sparks

## SPECIFICATIONS:

**INPUT CHARACTERISTICS:** AC INPUT: 90 - 264V AC **FREQUENCY:** 47Hz - 63 Hz

**INPUT CURRENT:** 50 WATTS **HOLD UP TIME:** 8mSEC

**PROTECTION:** INPUT FUSED .750 AMPS (OC) OVER CURRENT (OV) OVER VOLTAGE (SC) SHORT CIRCUIT (RP) REVERSE POLARITY

**OUTPUT CHARACTERISTICS:** 40.8 VDC 1.34 AMPS - 50 WATT (P/N 2365L-36)

**RIPPLE & NOISE** 120 mV or less

**ENVIRONMENT:** 0 - 40 DEGREES(C), 20 - 80% HUMIDITY

**WARRANTY:** 12 MONTH LIMITED WARRANTY

**DIMENSIONS:** 2.5 LBS - 5.75" X 3.25" X 1.75"



## Included Cables:

6' Alligator Clip-On Cable,  
6' Terminal LUG Cable  
6' AC Power Cable  
& Mounting Bracket

**GOLF CARTS,  
RVs & OTHER 36 VOLT SYSTEMS**



# GOLF CARTS, HYDRAULICS & OTHER 48 VOLT SYSTEMS

**50 WATT CHARGER, MAINTAINER & TESTER**

**48 VOLT**

**50 WATT**

**4 - 8 LARGE  
BATTERIES**

# CHARGERS

**& MAINTAINERS WITH BUILT-IN DIGITAL BATTERY TESTER**



#2365L-48

- Capable of Maintaining Several Batteries in a 48 Volt System
- Pulse Desulfation Technology -- Extends Battery Life
- Built-in LCD Digital Battery Tester (Tests The Battery, Load Tests & Tests The Charging System)
- Prevents Premature Battery Replacement with Proper Use
- Perfect for Long-Term Maintaining Once Maintainer Reaches FULL
- Works with SLA, GEL, Dry Cell, AGM, Deep Cycle, and Spiral Cell Batteries.
- Safe! Reverse Polarity Protection, No-Sparks

## SPECIFICATIONS:

**INPUT CHARACTERISTICS:** AC INPUT: 90 - 264V AC **FREQUENCY:** 47Hz - 63 Hz

**INPUT CURRENT:** 1.5 AMPS **HOLD UP TIME:** 8mSEC

**PROTECTION:** INPUT FUSED .750 AMPS (OC) OVER CURRENT (OV) OVER VOLTAGE (SC) SHORT CIRCUIT (RP) REVERSE POLARITY

**OUTPUT CHARACTERISTICS:** 54.4 VDC 1.04 AMPS - 50 WATT (P/N 2365L-48)

**RIPPLE & NOISE** 120 mV or less

**ENVIRONMENT:** 0 - 40 DEGREES(C), 20 - 80% HUMIDITY

**WARRANTY:** 12 MONTH LIMITED WARRANTY

**DIMENSIONS:** 2.5 LBS - 5.75" X 3.25" X 1.75"



**Included Cables:**

**6' Alligator Clip-On Cable,  
6' Terminal LUG Cable  
6' AC Power Cable  
& Mounting Bracket**