



MOTORCYCLES



ATVS



CLASSICS



JET SKIS



SNOWMOBILES



SMALLER CARS

12 WATT • 6 / 12 VOLT

SINGLE BATTERY APPLICATION

# MAINTAINERS

AUTOMATIC 6 & 12 VOLT APPLICATIONS. OPTIONAL BUILT-IN DIGITAL BATTERY TESTER (P/N #1200-LCD)

**MINI**



P/N: #1200



P/N: #1200-LCD

Perfect for  
Motorcycles,  
Jet Skis &  
Cars!

## 12 WATT PULSE MAINTAINER

With PULSE CLEANER Desulfation "Battery Extending" Technology!

The Battery Saver™ "1200" series is our 12 watt economical line of dual voltage maintainers. These models are physically the smallest we offer. They each feature our signature Auto-Pulse desulfation technology, micro processor control and can automatically recognize both 6 and 12 volt batteries and will switch to the correct charging setting when connected. Perfect for long term maintaining.



Works with Lead Acid, AGM, Gel, Dry Cell, Spiral Cell & Deep Cycle batteries!

Included Cables: 2' Alligator Clip-On 2' Terminal Lug 6' AC Power (Built-In)  
& Removable Mounting Bracket

Specifications:

INPUT CHARACTERISTICS: AC INPUT: 90 - 264V AC FREQUENCY: 47 Hz - 63 Hz INPUT CURRENT: .75 AMPS HOLD UP TIME: 8 mSEC

PROTECTION: INPUT FUSED 1 AMPS (OC) OVER CURRENT (OV) OVER VOLTAGE (SC) SHORT CIRCUIT (RP) REVERSE POLARITY

OUTPUT CHARACTERISTICS 06.8 VDC 1.25AMPS - 12 WATTS (P/N 1200) 13.6 VDC 1.08 AMPS - 12 WATTS (P/N 1200)

06.8 VDC 1.25AMPS - 12 WATTS (P/N 1200LCD) 13.6 VDC 1.08 AMPS - 12 WATTS (P/N 1200LCD)

RIPPLE & NOISE 120 mV or less ENVIRONMENT: 0 - 40 degrees(C), 20 - 80% HUMIDITY

WARRANTY: 12 MONTH LIMITED WARRANTY DIMENSIONS: 1.12 LBS - 4.0" x 2.5" x 1.5"

## 12 WATT PULSE MAINTAINER & TESTER

With PULSE CLEANER Desulfation "Battery Extending" Technology!

The 1200-LCD features a digital readout, in addition to all the maintaining functions of the (P/N #1200) that provides both the "charging voltage" and "amps" as well as having a lateral charging bar which graphically illustrates the percentage the battery is charged. It not only indicates the life left in a battery but it also checks the charging system by starting the vehicle while connected.



Works with Lead Acid, AGM, Gel, Dry Cell, Spiral Cell & Deep Cycle batteries!

Included Cables: 2' Alligator Clip-On 2' Terminal Lug 6' AC Power (Built-In)  
& Removable Mounting Bracket

Specifications:

INPUT CHARACTERISTICS: AC INPUT: 90 - 264V AC FREQUENCY: 47 Hz - 63 Hz INPUT CURRENT: .75 AMPS HOLD UP TIME: 8 mSEC

PROTECTION: INPUT FUSED 1 AMPS (OC) OVER CURRENT (OV) OVER VOLTAGE (SC) SHORT CIRCUIT (RP) REVERSE POLARITY

OUTPUT CHARACTERISTICS 06.8 VDC 1.25AMPS - 12 WATTS (P/N 1200) 13.6 VDC 1.08 AMPS - 12 WATTS (P/N 1200)

06.8 VDC 1.25AMPS - 12 WATTS (P/N 1200LCD) 13.6 VDC 1.08 AMPS - 12 WATTS (P/N 1200LCD)

RIPPLE & NOISE 120 mV or less ENVIRONMENT: 0 - 40 degrees(C), 20 - 80% HUMIDITY

WARRANTY: 12 MONTH LIMITED WARRANTY DIMENSIONS: 1.12 LBS - 4.0" x 2.5" x 1.5"