

CHARGERS

INDIVIDUAL VOLTAGE SPECIFIC CHARGER, MAINTAINERS. AVAILABLE IN 24, 36 AND 48 VOLT MODELS!

INDUSTRIAL



50 WATT PULSE CHARGER, MAINTAINER

With PULSE CLEANER Desulfation "Battery Extending" Technology!

The Battery Saver™ "2365" series offers our most powerful charging and maintaining capabilities. The different models have been designed to work optimally with that specific voltage battery or battery system. As is the case with all of our chargers and maintainers, these units have a built-in micro processor control to guarantee the quality of the charge and to ensure everything runs smoothly. Additionally, all of these units feature our AUTO PULSE desulfation technology to extend your battery's life.



Works with Lead Acid, AGM, Gel, Dry Cell, Spiral Cell & Deep Cycle batteries! Included Cables with all models: 6' Alligator Clip-On, 2' Terminal Lug, 10' AC Powe & Mounting Bracket

Specifications

INPUT CHARACTERISTICS: AC INPUT: 90 - 264V AC FREQUENCY: 47 Hz - 63 Hz INPUT CURRENT: 1.5 AMPS HOLD UP TIME: 8 mSEC PROTECTION: INPUT FUSED 2 AMPS (OC) OVER CURRENT (OV) OVER VOLTAGE (SC) SHORT CIRCUIT (RP) REVERSE POLARITY OUTPUT CHARACTERISTICS 13.6 VDC 4.17AMPS - 50 WATTS (P/N 2365) 27.2 VDC 2.08 AMPS - 50 WATTS (P/N 2365-24) 40.8 VDC 1.34AMPS - 50 WATTS (P/N 2365-36) 54.4 VDC 1.04 AMPS - 50 WATTS (P/N 2365-48) RIPPLE & NOISE 120 mV or less ENVIRONMENT: 0 - 40 degrees(C), 20 - 80% HUMIDITY WARRANTY: 12 MONTH LIMITED WARRANTY DIMENSIONS: 2.0 LBS - 5.75" x 3.25" x 1.75"



HYDRAULICS



AIRCRAFT



RVS



FORKLIFTS



SCOOTERS

